



KRAFT SELF-ADHESIVE PAPER

TECHNICAL DATA SHEET

TYPICAL APPLICATIONS & ADVANTAGES

- ✎ Kraft paper for a sustainable packaging.
- ✎ Medium and heavy duty carton sealing tape.
- ✎ Suitable either with a manual dispenser or automated application.
- ✎ **FSC C157528** certified adhesive tape.
- ✎ Certified recyclable, a repulpable paper tape at the end of its usage. It can be disposed into the blue paper recycling container, directly for recycling.*
- ✎ Paper manufactured from unbleached Elementary Chlorine Free (ECF) natural pulp.




CONSTRUCTION

- ✎ Backing: Premium FSC certified Kraft paper.
- ✎ Adhesive: Natural rubber from FSC certified forestry.
- ✎ Colour: Available in brown kraft or white.

TECHNICAL DATA

	METRIC
Paper Thickness	90 Micron
Total Thickness	110 Micron
Peel Adhesion	8,5 N/cm
Tensile Strength	45 N/cm
Application Temperature	6°C to 45°C
Service Temperature	-10°C / +60°C



Physical and performance characteristics shown above are obtained following tests recommended by AFERA. The values given are typical values and do not constitute a specification. The user should determine whether the tape is suitable for the intended application.

STORAGE

Tape performance is guaranteed within the first 6 months.
Product must be kept in its original box and in a dry atmosphere away from direct sunlight.

SECURITY

Product does not contain any dangerous or unhealthy components. Security data sheets are available based on directive 91/155/EC. All our tapes comply with European 2004/12/CE Packaging directive.